



FlexiKork™ is a flat, resilient underlayment that is used directly under a variety of floor finishes, yielding exceptional results especially under hard surface flooring and over concrete and wood joist construction.

FEATURES	BENEFITS
Made from 100% resilient recycled rubber and cork	Environmentally friendly , green product that meets LEED criteria.
Anti-Microbial	Prevents/inhibits the growth of microorganisms.
Truly universal underlayment	Compatible under most types of grouted and non-grouted flooring installations including ceramic tile, stone, solid & engineered hardwood, laminate, vinyl and carpet.
Can thin-set tile and stone directly to the product	No special tile/stone adhesive is needed. Can thin-set tile and stone directly to the product per ASTM C627. Saves time, labor and money!
Shock & stress relieving	Shock absorbing, flexible material with stress relieving capabilities, will not break down or move under load - strong enough for trades to work on. Prevents tile from cracking.
Superb sound control	Outperforms cork, felt, polyethylene, fiberglass and nylon matrix. Provides the highest IIC and STC rating backed by many independent laboratory and field tests.
Suitable for application in variety of housing	Extremely broad spectrum of uses in virtually every housing including: multifamily housing, high rises, single-family homes and commercial buildings.
Inhibits sound transfer through floor-ceiling assembly	Absorbs sound and vibration. Keeps noises from traveling through floor-ceiling assembly.
Increases IIC and STC ratings	Meets and exceeds tough building code requirements while adding less than 1/2" of floor height.
Suitable for all floor heating systems	Can be installed over radiant heating systems with no adverse effects.
Low construction height	Reduces gaps in floor when moving from one hard surface to another Saves space, reduces the use of transitional pieces as dif ferent surfaces can be the same height.
Available in two thicknesses	FlexiKork™ is available in 2 thicknesses: 3 mm (1/8") is available in 100 & 300 sq. ft. rolls 6 mm (1/4") is available in 120 sq. ft. roll.
Available in rolls for simple and fast installation	FlexiKork™ is available in 4' (48 inches) wide rolls for fast and easy installation. Rolls out quickly, stays in place and will not shift when laid. <i>Just roll out and go!</i>
Suitable for use with most polyurethane adhesives	FlexiKork™ can be glued down using most polyurethane adhesives, including recommended UZIN MK-97. Please see FlexiKork™ Installation Instructions (Part VII) for additional adhesive recommendations.



1171 Landmeier Road, Elk Grove Village, IL 60007 U.S.A.

Tel 866.554.4252 Fax 847.758.9696

www.FlexiKork.com

Info@FlexiKork.com